

CROSS-COUNTRY UTILITY

TECHNICAL SPECIFICATIONS



| PHYSICAL CHARACTERISTICS | | |
|--|----------------|---------------|
| Frame | Steel | |
| Cabinet | Aluminum | |
| Length | 72 1/4 in | 1835 mm |
| Width | 30 3/16 in | 767 mm |
| Height | 48 7/8 in | 1241 mm |
| Weight | 1583 lb | 718 kg |
| Ground clearance | 9 in | 229 mm |
| Turning diameter | 76 1/2 in | 1943 mm |
| Load bearing capacity (inclined surface) | 1600 lb at 40° | 725 kg at 40° |
| Load bearing capacity (on stairs) | N/A | N/A |
| Load bearing capacity (flat surface) | 1800 lb | 816 kg |
| Max. speed (flat surface) | 44 ft/min | 13.4 m/min |

| POWER | |
|----------------------------|--|
| Motor power | 1 HP (x2) |
| Gearbox ratio | 100:1 (x2) |
| POWER FEATURES | |
| Batteries Amperage/Voltage | 130 Amp at 12 volts (x4) |
| Charger | Integrated AC-DC with 120 volts inverter (x1) |
| Battery Pack Amperage | 260 Amp |
| Operating voltage | 24 VDC |
| Continuous Run-Time | Varies according to the operating conditions (Contact Movex Innovation for more information) |
| Battery Recharging Time | 10.5 hours approx. |
| Control | - Wired (standard) - Wireless (option) |

The information contained in this document is subject to change without notice.