

# TRACK-O 75

## TECHNICAL SPECIFICATIONS



| PHYSICAL CHARACTERISTICS                 |                |               |
|--|----------------|---------------|
| Frame                                    | Steel          |               |
| Cabinet                                  | Aluminum       |               |
| Length                                   | 76 in          | 1930 mm       |
| Width                                    | 30 in          | 762 mm        |
| Height                                   | 12 9/16 in     | 319 mm        |
| Weight                                   | 575 lb         | 261 kg        |
| Ground clearance                         | 2 1/16 in      | 52 mm         |
| Turning diameter                         | 77 1/2 in      | 1969 mm       |
| Load bearing capacity (inclined surface) | 1100 lb at 40° | 500 kg at 40° |
| Load bearing capacity (on stairs)        | 1100 lb at 40° | 500 kg at 40° |
| Load bearing capacity (flat surface)     | 1500 lb        | 680 kg        |
| Max. speed (flat surface)                | 22 ft/min      | 6.7 m/min     |

| POWER                      |  |
|----------------------------|--|
| Motor power                | 3/4 HP (x1)  |
| Gearbox ratio              | 200:1 (x1)   |
| POWER FEATURES             |  |
| Batteries Amperage/Voltage | 85 Amp at 12 volts (x2)  |
| Charger                    | Integrated AC-DC (x1)  |
| Battery Pack Amperage      | 85 Amp   |
| Operating voltage          | 24 VDC   |
| Continuous Run-time        | Varies according to the operating conditions (Contact Movex Innovation for more information) |
| Battery Recharging Time    | 5.5 hours approx.  |
| Control                    | - Wired (standard)<br>- Wireless (option)  |

The information contained in this document is subject to change without notice.