

# TWIN-TRACK 66HS HIGH SPEED

## TECHNICAL SPECIFICATIONS



PHYSICAL CHARACTERISTICS		
Frame (with rollers)	Steel (Aluminum)	
Cabinet	Aluminum	
Length	65 in	1651 mm
Width	30 in	762 mm
Height	13 3/4 in	349 mm
Weight	941 lb	427 kg
Ground clearance	2 1/8 in	54 mm
Turning diameter	70 in	1778 mm
Load bearing capacity (inclined surface)	1100 lb at 40°	500 kg at 40°
Load bearing capacity (on stairs)	1100 lb at 40°	500 kg at 40°
Load bearing capacity (flat surface)	2200 lb	1000 kg
Max. speed (flat surface)	164 ft/min	50 m/min

POWER	
Motor power	3.25 HP (x2)
Gearbox ratio	50:1 (x2)
POWER FEATURES	
Batteries Amperage/Voltage	130 Amp at 12 volts (x2)
Charger	Integrated AC-DC (x1)
Battery Pack Amperage	130 Amp
Operating voltage	24 VDC
Continuous Run-time	1.5 hours approx. (may vary depending on the utilization)
Battery Recharging Time	8.5 hours approx.
Control	- Wired (standard) - Wireless (option)

The information contained in this document is subject to change without notice.