

CROSS-COUNTRY UTILITY

TECHNICAL SPECIFICATIONS



PHYSICAL CHARACTERISTICS		
Frame	Steel	
Cabinet	Aluminum	
Length	72 1/4 in	1835 mm
Width	30 3/16 in	767 mm
Height	48 7/8 in	1241 mm
Weight	1583 lb	718 kg
Ground clearance	9 in	229 mm
Turning diameter	76 1/2 in	1943 mm
Load bearing capacity (inclined surface)	1600 lb at 40°	725 kg at 40°
Load bearing capacity (on stairs)	N/A	N/A
Load bearing capacity (flat surface)	1800 lb	816 kg
Max. speed (flat surface)	44 ft/min	13.4 m/min

POWER	
Motor power	1 HP (x2)
Gearbox ratio	100:1 (x2)
POWER FEATURES	
Batteries Amperage/Voltage	130 Amp at 12 volts (x4)
Charger	Integrated AC-DC with 120 volts inverter (x1)
Battery Pack Amperage	260 Amp
Operating voltage	24 VDC
Continuous Run-Time	4 hours approx. (without load, flat surface)
Battery Recharging Time	10.5 hours approx.
Control	- Wired (standard) - Wireless (option)

The information contained in this document is subject to change without notice.