

CROSSCOUNTRY HS

TECHNICAL SPECIFICATIONS



Model	Regular undercarriage	Flat undercarriage
PHYSICAL CHARACTERISTICS		
Frame	Steel	
Cabinet	Aluminum	
Length	72 1/4 in (1835 mm)	
Width	30 3/16 in (767 mm)	
Height	21 1/2 in (546 mm)	
Weight	1216 lb (552 kg)	
Ground clearance	9 in (229 mm)	6 7/8 in (174 mm)
Turning diameter	76 1/2 in (1943 mm)	
Load bearing capacity (Inclined surface)	1600 lb at 40° (725 kg at 40°)	
Load bearing capacity (On stairs)	N/A	925 lb at 40° (420 kg at 40°)
Load bearing capacity (Flat surface)	2292 lb (1039 kg)	
Max speed (Flat surface)	164 ft/min 50 m/min	

Model	Regular undercarriage	Flat undercarriage
POWER		
Motor power	3.25 HP (X2)	
Gearbox ratio	50:1 (x2)	
POWER FEATURES		
Battery pack configuration	2 x 12 Volts (series)	
Battery pack Amperage	130 Amp	
Operating voltage	24 VDC	
Run-time	Varies according to the operating conditions (Contact Movex Innovation for more information)	
Charger	Integrated AC-DC (x1)	
Battery recharging time	8.5 hours (approx.)	
Control	- Wired (standard) - Wireless (optional)	

The information contained in this document is subject to change without notice.