

TWIN-TRACK 66

TECHNICAL SPECIFICATIONS



PHYSICAL CHARACTERISTICS		
Frame (with rollers)	Steel	Aluminum
Cabinet	Aluminum	
Length	65 in	1651 mm
Width	30 in	762 mm
Height	13 3/4 in	349 mm
Weight	902 lb	410 kg
Ground clearance	2 1/8 in	54 mm
Turning diameter	70 in	1778 mm
Load bearing capacity (Inclined surface)	1760 lb at 32° 1100 lb at 40°	800 kg at 32° 500 kg at 40°
Load bearing capacity (On stairs)	1760 lb at 32° 1100 lb at 40°	800 kg at 32° 500 kg at 40°
Load bearing capacity (Flat surface)	2200 lb	1000 kg
Max speed (Flat surface)	44 ft/min	13.4 m/min

POWER	
Motor power	1 HP (x2)
Gearbox ratio	104:1 (x2)
POWER FEATURES	
Battery pack configuration	2 x 12 volts (series)
Charger	Integrated AC-DC (x1)
Battery pack Amperage	130 Ah
Operating voltage	24 VDC
Run-time	Varies according to the operating conditions (Contact Movex Innovation for more information)
Battery recharging time	7 hours approx.
Control	- Wired (standard) - Wireless (option)

OPTIONAL
GEARBOXES 75:1, SPEED 60 FT/MIN (18 M/MIN)

The information contained in this document is subject to change without notice.