

E-SCOUT EL-2650

TECHNICAL SPECIFICATIONS



Features			
Electric powered	✓	Motor brake	✓
Remote controlled	✓	Linear speed control	✓
Modular platform	✓	Switchable LED lighting (front & rear)	✓
Switchable Motion Alarm	✓	Maintenance Free AGM Batteries	✓
CAN bus communication	✓	Upgradable and configurable software	✓
Auxiliary output socket	✓	12V & USB Ports	✓
Multi-axial Grade monitoring	✓	On-board tracking & diagnostics	0

PHYSICAL CHARACTERISTICS

Frame	Steel
Cabinet	Steel
Length	46 1/2 in (1185 mm)
Width	29 1/2 in (750 mm)
Height	15 3/4 in (399 mm)
Weight	750 lb (340 kg)
Ground clearance	2 1/8 in (54 mm)
Turning diameter	approx. 53 1/4 in (1352 mm)

PERFORMANCE

Load bearing capacity (Leveled surface)	2650 lb (1202 kg)
Zero-Turn Capacity	Yes

POWER

Motor power	1.6 HP (X2)
Battery pack configuration	2 x 12 Volts (series)
Battery pack Amperage	115 Ah
Operating voltage	24 VDC
Run-time	Varies according to the operating conditions (Contact Movex Innovation for more information)
Charger	Integrated AC-DC (x1) 110V-230V
Control	Wireless Linear

Notes :

1. The information contained in this document is subject to change without notice.